

Great Awareness, Easy Control



Save Cable Wiring

One USB cable for control and power

Smart Design

Milky lens that harmonizes with every environment





Terminal Connection
Display status for self-checkout and similar systems



Built into Equipment
Status notification of PC controlled equipment like printers.



PC Connection
Interlock software alarm

Various Mounting Methods

NE-SN-USB

Magnet mounting



1/4-inch screw mounting

*Obtain tripod separately.



NE-WN-USB

Pole bracket
NE-001D



Wall mounting bracket
NE-002D



1/2" NPT Bracket
SZP-092D



*Mounting example

Easy Control with Software Library

- Easy control by using the software library downloaded from our website.
(Control can also be made according to protocol specifications for operating systems other than the supported ones.)
- Demo apps and sample codes can be downloaded from our website.

Dedicated Driver not Required

- Control is possible without installing dedicated drivers because it is an HID class device.

Specifications

Model		NE-SN-USB	NE-WN-USB
Rated voltage		DC5V (USB bus power)	
Operating Voltage Range		Rated voltage ±5% (conforms to USB 2.0 standard)	
Rated Current Consumption	Maximum	205mA	170mA
	Conditions	Lighting Color: White Alarm Sound: Alarm pattern "No.1 continuous sound" Volume Level: Maximum	
Operating Ambient Temperature		-20°C to +50°C	-25°C to +60°C
Operating Ambient Humidity		90% RH or less, non-condensing	
Mounting Location		Weather protected location	
Mounting Direction		All directions	All directions (Upright only when waterproofing is required)
Protection Rating		IP20	IP65
Sound Pressure		Typ. 65dB	Typ. 85dB
Environmental Conditions		Facing forward; 0.5m from front of unit Alarm pattern: "No.2 sweep sound"	Facing forward; 1m from front of unit Alarm pattern: "No.2 sweep sound"
Luminous Color		Multi-color (7 colors) (Red, Green, Blue, Amber, Cyan, Purple, White)	

Model Number Configuration


NE- N-USB

Specifications


S : Stationary/Magnet mounting/1/4 inch Screw mounting
W : 2-point hole screw mounting

External View (mm)

■ NE-SN-USB




■ NE-WN-USB



<Mounting dimension drawing>

■ 2-point hole screw mounting (NE-WN-USB)



PATLITE Corporation

PATLITE (U.S.A.) Corporation

PATLITE KOREA CO., LTD.

PATLITE (SINGAPORE) PTE LTD

PATLITE MEXICO S.A. de C.V.

PATLITE TAIWAN CO., LTD.

PT. PATLITE INDONESIA

PATLITE Europe GmbH

PATLITE (THAILAND) CO., LTD.

PATLITE UK LTD

PATLITE (CHINA) Corporation

www.patlite.com

●PATLITE, the PATLITE logo are either registered trademarks or trademarks of PATLITE Corporation in JAPAN and/or other countries.

O-BB02A EN 2208 A